

SPF 4~12KT HVM

- Integrated MPPT charge controller
- Optional WIFI/ GPRS remote monitoring
- Built-in pure copper low frequency transformer
- Configurable grid or solar input priority



P O W E R
- I N G O
T O M O -
R R O W O

GROWATT

www.ginverter.com

Datasheet	SPF 4KT HVM	SPF 5KT HVM	SPF 6KT HVM	SPF 8KT HVM	SPF 10KT HVM	SPF 12KT HVM
Battery Voltage	48VDC	48VDC	48VDC	48VDC	48VDC	48VDC
Battery Type	Lithium/Lead-acid	Lithium/Lead-acid	Lithium/Lead-acid	Lithium/Lead-acid	Lithium/Lead-acid	Lithium/Lead-acid
INVERTER OUTPUT						
Rated Power	4KW	5KW	6KW	8KW	10KW	12KW
Surge Rating	12KW	15KW	18KW	24KW	30KW	36KW
Waveform	Pure sine wave/ same as input(bypass mode)					
Nominal Output Voltage RMS	220V/230V/240VAC(+/-10% RMS)					
Output Frequency	50Hz/60Hz +/-0.3 Hz					
Inverter Efficiency(Peak)	>85%			>88%		
Line Mode Efficiency	>95%					
Power Factor	1.0					
Transfer Time	10ms typical , 20ms Max					
SOLAR CHARGER						
Maximum PV Charge Current	80A			120A		
Maximum PV Array Power	5000W			7000W		
Number of independent MPP trackers/ strings per MPP tracker	1/1			2/1		
MPPT Range @ Operating Voltage	60~145VDC					
Maximum PV Array Open Circuit Voltage	150VDC					
Maximum Efficiency	>98%					
AC INPUT						
Voltage	230VAC					
Selectable Voltage Range	154~272VAC(for appliances);184~272VAC(for UPS)					
Frequency Range	50Hz/60Hz (Auto sensing)					
Maximum Charge Current	40A	50A	60A	70A	80A	100A
MECHANICAL SPECIFICATIONS						
Protection Degree	IP20					
Dimensions (W/H/D)	360/540/218mm			380/650/255mm		
Net Weight (Solar CHG) kg	38	41	45	64	66	75
OPERATING ENVIRONMENT						
Operation Temperature Range	0°C to 45°C					