

REVO residential energy storage inverters

Split-phase Hybrid Inverter



Key strengths

- ! Mainstream battery automatic matching.
- ! Support remote software upgrade.
- ! Supporting critical load priority power supply.
- ! UL certified, CEC listed and SUNSPEC listed.
- ! Single machine bypass with load of 90A.
- ! Support 100% unbalanced load capacity.

Applications

- » Luxury villa
- » Residential nomadic farm electricity
- » Nomadic farm
- » Communication base station

REVO residential energy storage inverters

PV string input

Model	R6KH1NA	R8KH1NA	R10KH1NA	R12KH1NA
Max. power (kW)	7.8	10.4	13	15.6
Max. DC voltage (V)	500			
MPPT voltage range (V)	125~500			
Max. input current of single MPPT (A)	12			
No. of MPPT trackers	4			
No. of strings per MPPT trackers	1			

AC output

Rated output power (kVA)	6	8	10	12
Max. apparent Power (kVA)	6.6	8.8	11	12
Max. output current (A)	27.5	36.7	45.8	50
Grid voltage/range (V)	240/211~264			
Frequency (Hz)	50/60			
PF	0.8lagging-0.8leading			
THDi	<3%			
AC output topology	Split phase, single phase			

Battery

Battery voltage range (V)	85~400			
Max. charging voltage (V)	400			
Full battery voltage (V)	85	110	140	160
Max. charge/discharge current (A)	80/80			
Battery type	lithium /Lead-acid			
Communication interface	CAN			

EPS output

Rated power (kVA)	6	8	10	12
Rated output voltage (V)	220-240 /110-120			
Rated frequency (Hz)	50/60			
Automatic switching time (ms)	<20			
THDu	<2%			
Overload capacity	110%,30S/120%,10S/150%,0.02S			

General data

Max. efficiency	≥98.2%			
CEC efficiency	≥97.2%			
Ingress protection	IP65/Type 4			
Noise emission(dB)	<25			
Operation temperature (°C)	-25 ~ 60			
Cooling	Natural			
Relative humidity	0 ~95% (non-condensing)			
Operation altitude	2,000m(>2,000 Derating)			
Dimensions W*D*H (mm)	530*200*660			
Net weight (kg)	32			
Self-consumption at night (W)	<20			

Display and communication

Display	LCD			
Interface:RS485/Wifi/4G/CAN	Yes/Opt/Opt/Yes			
Safety standard	UL1741SA all options, UL1699B, CSA 22.2			
EMC	FCC Part 15, Class B			